

Portable split air conditioner

R290 · 12,000 BTU/h

Cooling. Heating. Flexible.

A mobile split solution with separate indoor and outdoor units. Cooling, heating, fan and dehumidification. Five fan speeds from Turbo to Silent.

Model: MKS6130031



3.5 kW*

Cooling & heating

105 m³

Room volume

R290

Refrigerant

Performance at a glance

Cooling / heating capacity*

3,500 W / 12,000 BTU/h each

SEER / SCOP*

6.1 / 4.0

Energy class cooling / heating*

A++ / A+

Indoor noise level

39-51 dB(A)

Refrigerant / charge

R290 / 360 g

* Provisional manufacturer data. Final values are subject to the certification report.

Technical specifications

Portable split air conditioner / MKS6130031

01 Performance & power supply*

Cooling capacity	3,500 W / 12,000 BTU/h
Heating capacity	3,500 W / 12,000 BTU/h
Power supply	220-240 V / 50 Hz
Rated input cooling / heating	1,250 / 1,150 W
Rated current cooling / heating	5.5 / 5.1 A
SEER / cooling energy class	6.1 / A++
SCOP / heating energy class	4.0 / A+
Refrigerant / charge	R290 / 360 g

02 Airflow & noise

Fan speeds	Turbo / High / Mid / Low / Silent
Indoor airflow ¹	450 / 420 / 370 / 320 / 245 m³/h
Indoor noise level ¹	51 / 48 / 46 / 42 / 39 dB(A)
Outdoor noise level	57 dB(A)
Ambient temperature cooling / heating	0 to 45 °C / -10 to 24 °C

03 Dimensions & logistics

Indoor unit (W × H × D)	430 × 730 × 320 mm
Outdoor unit (W × H × D)	492 × 460 × 263 mm
Package (W × H × D)	695 × 890 × 575 mm
Net weight indoor / outdoor	22.0 / 9.5 kg
Total net / gross weight ²	34.5 / 43 kg
Recommended room volume	105 m³
Container loading (40' HQ)	202 sets

¹ Order: Turbo / High / Mid / Low / Silent.

² Total net weight including the connecting line: 34.5 kg.

* Cooling and heating data are provisional. Final values are subject to the certification report.

Manufacturer specifications. Product image with LuxProof branding is illustrative.